



WEST COAST MONUMENT & SIGN LLC D.B.A.
CCB 154861
PO BOX 73 MYRTLE POINT, OR 97458.
OFFICE: 541-572-5228/FAX 541-559-1167

FAQ

Which is better granite or quartz?

One is not better than the other. For more information on the differences, please check out our Quartz VS Granite page. The primary difference is color and pattern.

Which is more expensive quartz or granite and what is the price of granite and quartz?

For quartz, it all depends on the brand of quartz and color. For granite, it depends on the availability. Prices range from \$70 per square foot installed up to \$200+ per square foot installed.

Granite needs a sealer. How long does that last for? Does Quartz need a sealer?

Our granite sealer lasts for 20 years if it has been properly cared for. We will provide you with a care guide for cleaning and maintaining your natural stone. Most Quartz do not require sealing. We have a list in our office of the brands and colors that require a sealer. We also have care guides for our engineered (Quartz) stone.

What is marble like?

Marble is softer than quartz or granite but not all marble is of the same hardness/softness. This is the main aspect to take into consideration when considering marble.

What is the first step?

Select a product and get a quote

What all is included in the estimate price?

The cost of the stone, templating, fabrication and installation are all included in the estimate, as well as certain edge details.

How is the stone price estimated?

By square feet.



WEST COAST MONUMENT & SIGN LLC D.B.A.
CCB 154861
PO BOX 73 MYRTLE POINT, OR 97458.
OFFICE: 541-572-5228/FAX 541-559-1167

Do you tear out our old countertops?

No, we do not.

Can you still template with my old countertops?

Yes. However, they will need to be removed by you or your contractor before install.

Do we need to bring you our sinks?

We get the sinks at time of template. Make sure the sink specs fit the cabinet.

Is it safe to set hot objects directly on the stone?

We do not recommend it. We recommend using a trivet.

How long does fabrication take?

Fabrication depends on the square footage of your job.

When is the remaining balance due?

The day of installation.

What is the thickness of the stone?

Most commonly used stone is 3cm (1 ¼" +/- ⅛")

What about 2cm stone?

2cm stone requires sub-decking. The homeowner, contractor, or cabinet maker is responsible for sub-decking. We suggest plywood for a sub-deck.

We do not do plumbing, electrical, or gas work.